

PRODUCT DATASHEET

BERRAKURE P

PVA Based Curing Compound

DESCRIPTION

BERRAKURE P is a high solid, polymer emulsion specifically formulated for the curing of concrete. The specially selected polymers contained in **BERRAKURE P** produce a fast drying membrane without the potential compatibility problems that can occur with wax or solvent based coatings.

BERRAKURE P contains a fugitive dye (white). The dried coating becomes clear within a few hours of application.

BENEFITS

- Dries to a clear finish
- Totally water based
- Reduces plastic shrinkage
- Meets low VOC requirements
- Can be applied by spray, roller or brush
- Will not yellow in sunlight
- Eliminates the need for curing by ponded water, damp hessian or polythene sheeting
- Seals concrete surfaces
- Takes most after trades
- (Adhesion test to be conducted prior)
- Equipment washable in water

APPLICATION RATE

Coverage: 5-8m² per litre

Tack Free: 30 mins

Hard Dry: 4 hours

Trafficable: 12 Hours

Application Temp: 10°C - 35°C

Application Method: Spray, Brush, Roller, Broom

APPLICATION

Apply **BERRAKURE P** to the concrete as soon as the bleed water has gone and the concrete has hardened sufficiently so as not to be marked by the application process.

Apply **BERRAKURE P** undiluted at a rate of between 5 and 8m² per litre. Best applied by spray, however, may also be applied by brush, roller or broom.

NOTE: Ensure all equipment is thoroughly cleaned in water.

Any advice, recommendation, information, assistance or service provided by application is in good faith and is believed by BERRA CONSTRUCTION PRODUCTS PTY LTD to be appropriate and reliable. However, any advice, recommendations, information, assistance or service provided is provided without liability.

TYPICAL PROPERTIES DATA

Appearance: White Milky Emulsion

Coverage: 5-8m² per litre

Form: Liquid

Flash Point: Not applicable

Application Temp: 10°C - 35°C

Solubility in Water: Totally Soluble

Solids: 27% +/- 1%

Shelf Life: 12 months max

Solvents: N/A

UN Number: N/A

Hazchem Code: N/A

Packaging Group: N/A

Poison Schedule: N/A

Dangerous Goods Class: N/A

FIRST-AID MEASURES

General advice:

Remove contaminated clothing.

If inhaled:

If difficulties occur after vapor has been inhaled, remove to fresh air and seek medical attention.

Skin contact:

Wash immediately with plenty of water and soap. Under no circumstances should organic soap be used. If irritation develops, seek medical advice.

Contact with eyes:

Wash affected eyes for at least 15 minutes under running water with eyelids held open, seek medical attention/consult an eye specialist.

EMERGENCY CONTACT

BERRA Construction Products:

+612 5105 1426

Poison Information Centre:

131 126

Any advice, recommendation, information, assistance or service provided by application is in good faith and is believed by BERRA CONSTRUCTION PRODUCTS PTY LTD to be appropriate and reliable. However, any advice, recommendations, information, assistance or service provided is provided without liability.