

ECOTAC® CLASSIC PVD BLACK STAINLESS STEEL (316)

**P5
GRIP**

TYPE	Tactile Ground Surface Indicator
RANGE	Warning Tactile
DESIGN	Classic Ecotac®
MATERIAL	316 marine grade stainless steel
FINISH	Machined
DIMENSIONS	OUTER DIA: 35mm TOP DIA: 25mm THICKNESS: 5mm



FEATURES

Machined, concentric circle design on the horizontal face with a smooth outer edge

An environmentally friendly alternative to the solid classic tactile, featuring a cupped underside that uses less stainless steel putting less demand on resources

Identical to the DTAC solid tactile when installed

Complies with the NCC (D3.8 Tactile Indicators) and Disability (Access to Premises—Buildings) standards to meet the deemed-to-satisfy-provisions

Complies with slip resistance requirements as detailed in HB 198

Backed by 2 year warranty

Registered design

SLIP RESISTANCE TESTING

Important information: To determine a classification of a slip resistance rating, see Australian Standards Hand Book 198 (HB 198), a Guide to the specification and testing of slip resistance of pedestrian surfaces. This document outlines the minimum ratings of a location and situation of a pedestrian surface.

TEST	AS 4586 APPENDIX A: Wet Pendulum Test
FOUR S 96 SLIDER	= 91 CLASS = P5
TRL 55 SLIDER	= 80 CLASS = P5

LUMINANCE TESTING

Important information: To determine a luminance contrast between a substrate and the DTAC TGSI, see: AS/NZS 1428.4.1:2009. DTAC can test your substrate for luminance contrast to give you peace of mind that your DTAC project will be fully compliant to AS/NZS 1428.4.1 Appendix E.

TEST	AS/NZS 1428.4.1 APPENDIX E PARAGRAPH E3
LUMINANCE REFLECTANCE RATING / WET	= 7.1
LUMINANCE REFLECTANCE RATING / DRY	= 8.7

DTAC PTY LTD
ABN 41 093 070 127

Unit 4, 11-12 Phillip Court
Port Melbourne Victoria
Australia 3207

PO Box 5059
South Melbourne Victoria
Australia 3205


T 1300 793 478
F 1300 780 628

estimating@dtac.com.au
www.dtac.com.au

© DTAC Pty Ltd 2020

ECOTAC® CLASSIC PVD BLACK INSTALLATION & APPLICATION

SUBSTRATE Stone / Masonry / Timber / Vinyl




CODE DT0122

FIXING Drill and pressure fit
(M8 x 25mm hole)

NOTE Any thick substrate
where maximum hold is
required without chemical
anchoring

SUBSTRATE Vitrified Porcelain / Ceramics / Glass / Metals



CODE DT0122

FIXING Diamond core/pressure fit
(M8 x 25mm hole)

NOTE Any thick substrate
where maximum hold is
required without chemical
anchoring