



SHIELDCOAT PTY LTD
Unit 2/1075 Beaudesert Rd, Archerfield Q 4108
Phone: (07) 3274 6911 Fax: (07) 3274 6414
Email: info@shieldcoat.com.au Web: www.shieldcoat.com.au

Product Information: **ROOFBOND FLEXIBLE POINTING**
Flexible pointing for tile ridges

Shieldcoat's **Roofbond Flexible Pointing** system uses an all acrylic binder specifically recommended for new roof and roof refurbishment applications. It is manufactured in Australia specifically for our unique and demanding climate.

Shieldcoat has chosen the best resin available on the market for this product. The criteria for Shieldcoat's choice is based on the resin's characteristics including durability, wet adhesion properties, gloss retention, low dirt pick up, low water sensitivity and through dry capabilities.

The resin chosen for the system is based on a highly UV resistant pure acrylic technology which has been an industry bench mark for adhesion and colour retention for over 25 years. Its durability and performance have been proven over many harsh Australian seasons. Whilst its cost is premium it will always remain the choice because of its quality and consistency.

The level of binder (resin) used in this formulation has been chosen to provide excellent through film build for a sound quality finish. The resin has enhanced wet adhesion and excellent fast through dry properties.

The product has proven itself in the area of dry hold down, especially in high wind areas such as Australia's eastern seaboard.

The product conforms to CSIRO AS2050 appendix F to a C3 rating.

Some key features and benefits of **Roofbond's** unique formulation are:

- ❖ Fast hardness development
- ❖ Good water resistance
- ❖ Excellent resistance to water whitening (blanching)
- ❖ Excellent exterior durability
- ❖ Enhanced wet adhesion properties.
- ❖ Solid dry hold down
- ❖ Very easy trowel application and fine finish.

Shieldcoat's commitment to consistent quality means that even their colours are produced in the factory to their own rigid requirements. **Bayer** pigments have been chosen for their durability and all are listed as 8 on a scale of 1-8 (ratings for Xenotest exposure. Grading = 1 poor 8 = excellent). This control over the entire production means that Shieldcoat is able to produce if colours specific to customer requirements. For applications where roof to be painted is used for collecting drinking water, ensure at least seven (7) days or the first rain before reconnecting downpipes.

Shieldcoat is firmly committed to providing product and service of the highest quality and consistency.

Last modified on: 31/12/02

DISCLAIMER

These suggestions and data are based on information we believe to be reliable. They are offered in good faith, but without guarantee, as conditions and methods of use of our products are beyond our control. We recommend that the prospective user determine the suitability of our materials and suggestions before adopting them on a commercial scale.